

HYDRASHELL SUPREME SA

HIGH TEMPERATURE ICE AND WATER PROTECTION



The best choice in high-temp, easy-to-handle, self-adhering applications. As Marco's superior underlayment, this peel and stick, self-adhering solution provides superior leak protection.

HydraShell Supreme SA helps to protect a building's deck or internal structure against leaks caused by ice and water damming and wind-driven rain.

HydraShell Supreme SA is a peel and stick, self-adhering solution that provides superior leak protection for standard roofing areas plus valleys, ridges, coping

joints, chimneys, vents, formers, skylights and low-slope sections. Exceptionally durable and pliable, HydraShell Supreme SA adheres to a wide variety of substrates. The split-back release film peels off easily to simplify installation, while a cool-gray surface to reduce heat build-up and a 90-day UV exposure rating for extended installation periods eases the process as well.

- Split-back release film peels off for easy installation
- Adheres to a variety of substrates

- Polymer-modified asphalt gives excellent pliability
- Exceptionally durable high-tensile/tear strengths
- Cool Gray surface to reduce heat build-up
- 90-day UV exposure rating
- 30-year limited warranty
- Made in the USA



30
YEAR
LIMITED WARRANTY



Roofing Ventilation & Accessories

The Marco Weather-Tite™ System

- Closure
- Ventilation
- Fasteners
- Flashing
- Sealants
- Underlayment
- Accessories

- ▶ Value drives everything we do. That's why we developed the Marco Weather-Tite System—a comprehensive line of products that offers easy installation, remarkable building ventilation, lower utility costs, extreme durability, and outstanding warranties. Get more quality, more performance and more value ... from Marco.



Specs

- Roll Dimensions: 36"x 67'
- Roll Weight: 55 lbs
- Area Per Carton: 201 ft²
- Cartons Per Pallet: 30
- Permeability (ASTM E96): .067 perms
- Nail Sealability (D1970): Pass
- Adhesion To Plywood @ 75° F (D903): >12 lbs/ft
- Adhesion To Plywood @ 40° F (D903): >2 lbs/ft
- Mill Thickness (ASTM D5147): 44
- Flexibility At -20° F (D1970): Pass
- High Temperature Rating: 240° F

You May Also Need

- ▶ Roof Boots™ / Weather-Tite Metal Roof Sealant

Easy Install

See our installation instructions online at MarcoIndustries.com. HydraShell Supreme SA features a split-back release film that peels off for easy installation. The clean, easy-to-handle, self-adhering application makes installation quick and efficient.



Step 1:

Tack/secure the end of the roll with a nail. Unroll the membrane 3-6 feet.



Step 2:

Carefully remove the upper release liner, align the membrane and continue to peel the release liner from the membrane. Stop frequently to press the membrane in place with heavy hand or roller pressure.



Step 3:

When finished with the desired length, repeat the process at the starting point by removing the remaining poly release film and pressing the membrane in place with heavy hand or roller pressure. Side laps (horizontal laps) must be a minimum of 3 inches and end laps a minimum of 6 inches.



Roofing Ventilation & Accessories

800.800.8590 / MarcoIndustries.com



Marco's Rapid Response™ delivers, faster and easier. Take advantage of free shipping with low minimum orders.