

TILE GOOSENECK VENT

**THE ONLY
GOOSENECK VENT
OF ITS KIND TO PASS
WIND-DRIVEN
RAIN TEST**

*Round design
for superior
utility exhaust*



*Mini louvers allows exhaust
while keeping water out*

*Enclosed design
eliminates water
infiltration*

Marco's Tile Gooseneck Vent is suitable for tile, synthetic, cedar, shake, and slate roofs.

The Tile Gooseneck Vent is the only vent of its kind to pass wind-driven rain testing. It's made from durable 26-gauge galvalume steel and its low vent profile and fully closed design can help reduce wind uplift. The Tile Gooseneck Vent has a round design that promotes superior airflow and makes it ideal for kitchen or bathroom exhausts.

- ▶ Quiet - no noisy damper opening and closing
- ▶ Does not allow water infiltration
- ▶ Suitable for any roof pitch from 3/12 to 12/12
- ▶ Mini louvers in vent hood block wind driven rain
- ▶ Interior louver panel captures any moisture directing it to the vent pan away from the attic
- ▶ Internal baffle offers a third line of defense against wind-driven rain
- ▶ Keeps insects and critters out
- ▶ Meets Energy Star color requirements
- ▶ High Quality & Durability - Reduces customer call-backs

**Not to be used as a laundry vent.*



Roofing Ventilation & Accessories

The Marco Weather-Tite™ System

Closure

Ventilation

Fasteners

Flashing

Sealants

Underlayment

Accessories

- Value drives everything we do. That's why we developed our Steep Slope Ventilation Division. This comprehensive line of products offer easy installation, remarkable building ventilation, lower utility costs, extended shingle and roof deck life, extreme durability, and outstanding warranties. Get more quality, more performance, and more value... Marco Industries.™

Specs

Dimensions: Width 19-3/16" x Height 10-1/4"

Materials: 26 - gauge galvalume

Codes & Standards: FL Building Code,

Color: Mill and Colors on request

Roof Pitch: Conforms to any pitch from 3/12 to 12/12

Patents: Pending

Sizes: 4", 6" and 10"

Vent Hood: Mini louvers in lower portion of hood block water



Proudly Made in North America



Interior Louver Panel: Mini louvers in opposite direction to louvers on lower portion of hood as second water barrier

Internal Baffle: Placed at the top of the vent pan, the internal baffle is the third line of defense against water intrusion

Easy Install

See our installation online at marcoindustries.com

1. Select required vent size; 4" Vent, 6" Vent, or 10" Vent
2. When installing vents on an existing tile roof: remove tiles immediately around sides and top of opening to provide space to install vent as per instructions below.
3. Position vent over opening in deck.
4. Fasten side and top flanges securely with minimum 1¼" standard roofing nails spaced 4" on center and 1½" from outer edge of flange.
5. Seal flanges to sub-roof membrane as per substrate manufacturer recommendations.
6. Cut tile to fit around vent and install per tile manufacturer recommendations.



High Profile
Tile Gooseneck Vent



Low Profile
Tile Gooseneck Vent



Roofing Ventilation & Accessories

800.800.8590 / MarcoIndustries.com



Marco's Rapid Response™ delivers, faster and easier. Take advantage of free shipping with low minimum orders.