



Roofing Ventilation & Accessories

MarcoFlex™

WEATHER-TITE™ • GUNNABLE BUTYL

A NON-SKINNING / NON-HARDENING BUTYL SEALANT THAT PROVIDES EXCELLENT ADHESION



MarcoFlex is a versatile ever-flexible sealant suitable for metal roofing, architectural panels, window glazing, expansion joints, flashing, and other bonding applications.

Features:

- ▶ Excellent Chemical Resistance
- ▶ Permanently Flexible
- ▶ Non-Corrosive to Metals
- ▶ Excellent Adhesion to Oily Metal Surfaces and Other Materials
- ▶ Low Shrinkage
- ▶ Ideal for use as Seam Sealant in Roll Forming Applications
- ▶ Safe for use on Kynar 500, Zincolume, Galvalume, Aluminum, and most other Metals

Technical Information:

| PROPERTIES | VALUE-RESULT | TEST METHOD |
|-------------------|----------------------------|---------------------------|
| Weight: | 12-13 lbs./gal. | ASTM D71-72 |
| Color: | Tan or Light Gray | Internal Lab |
| Order: | Light Solvent | Internal Lab |
| Solids Content: | 90% +/- 2% | ASTM C771-74 |
| Vaper Transfer: | <1 gram/day | ASTM D96 |
| Flashpoint: | >102f - non-red label | ASTM D93-79 |
| Slump: | Max 3/16" @ 210f | ASTM D2202 |
| Water Absorption: | None | GSTM 21 |
| Weathering: | None at 1000 hrs. | UV Light / Sunlamp |
| Service Temps: | -40°F/-40°C to 249°F/120°C | |
| Storage Temps: | 0°F/-18°C to 100°F/38°C | *store in clean, dry area |
| Shelf Life: | 18 months | |

EXPAND YOUR ROOFING SYSTEM PERFORMANCE
PREVENT LEAKS • PROTECT PROPERTY • ASSURE VENTILATION